



MATWORKS

COMPREHENSIVE FLOORING SOLUTIONS

Comfort Flow

Comfort Flow™ mats are highly durable slip-resistant mats best suited for wet environments. They are versatile, so they can be placed where grease, oil, and chemicals may be present. Comfort Flow features drainage holes that allow liquids to pass through. The nitrile rubber cushion provides excellent anti-fatigue qualities and features a lifetime anti-microbial treatment that helps prevent odors and degradation to the mat. Unlike traditional floor mats, which are typically heavy and difficult to move, Comfort Flow has a flexible design that makes it easy to roll, handle, clean, and store.



PRODUCT INFO

Anti-Fatigue Matting



Specifications	
Material	Closed cell nitrile rubber foam
Overall Thickness	3/8"
100% Customer Satisfaction* <small>*Based on the life of the product</small>	

Size(s)	
Size (ft.)	Size (in.)
2' x 3'	23" x 34"
3' x 5'	34" x 56"
3' x 9'	34" x 109"
4' x 6'	42" x 68"
Mat sizes are approximate as rubber shrinks and expands in conjunction with temperature and time. Tolerable manufacturing size variance is 3-5%.	

Standards & Testing	
Durometer	45
Compression Deflection	43.8% at 20 psi 55.7% at 40 psi
ASTM C1028-96 static coefficient of friction	Dry 1.00 Wet 0.91
ESD rating of static dissipative	Surface to surface at 50% relative humidity 2.0 X 10 ⁹ ohms Surface to surface at 12% relative humidity 2.5 x 10 ⁹ ohms
Certified high-traction by the National Floor Safety Institute (NFSI)	
Passes flammability standard DOC-FF1-70	
Passes fungal resistance standard ASTM G21	

CLEANING INSTRUCTIONS

- Scrub with a deck brush (as needed), using a detergent with a neutral pH, or rinse with a hose or pressure washer. Hang mat to dry.
 - Comfort Flow mats can be folded and washed in a commercial dishwasher*
 - Always make sure the mat is dry before placing it back in service
- *Please check your local health code for restrictions

