



MATWORKS

COMPREHENSIVE FLOORING SOLUTIONS

Diamond II Logo Mats

Diamond II Logo mats feature your custom logo or message inlaid into the attractive Berber-constructed mat. They are ideal for large areas or custom applications. The heavy solution-dyed fabric is stain resistant and has excellent light fastness making them tough enough for heavy foot traffic or outdoor use. The high-performance rubber backing helps hold the mat in place to minimize slipping hazards.



PRODUCT INFO

Indoor/Outdoor Logo Entrance Matting



Sewn Vinyl Edging

Singed Edging

17 Standard Color Options



Colors may vary due to inconsistencies of various display monitors or printers (if you're viewing a printed version of this document).

Color images are intended to be used as a guide only.

CLEANING INSTRUCTIONS

- Vacuum regularly: daily in high-traffic areas, weekly in lower-traffic applications
- Extract or hose off as needed to remove heavy soil/debris
- Always make sure the mat is dry before placing back into service



Specifications

Material	Solution-dyed polypropylene
Material Weight	52 ounces/yard ²
Construction	Needle-punched
Design	Hobnail
Backing	Performance rubber
Overall Thickness	3/8"
*100% Customer Satisfaction *Based on the life of the product	

Size(s)

Custom sizes are available in the following widths up to 50' in length. Please note that widths over 6' may be seamed based on material availability.

3'
4'
5'
6'
7'
8'
9'
10'
11'
12'

Note: The width must be in one of the whole foot increments listed above.

Mat sizes are approximate as rubber shrinks and expands in conjunction with temperature and time. Tolerable manufacturing size variance is 3-5%.

Design Specifications

Berber Roll Goods Logo mats are produced using an inlay process, where colored material is cut and pieced together by hand before pressing into rubber. As a result, there are very strict design requirements for this product. PMS color matching is not available

Minimum Text Height	3"
Minimum Line Thickness	3/8"

Any space between letters or design elements must be at minimum 3/8". The text requirements are for general use; however, special fonts and very thin letter forms may need to be made larger or thicker and will be approached on a case-by-case basis.

Gradients, tints, screens and transparencies are not supported and should not be used.