MATWORKS
COMPREHENSIVE FLOORING SOLUTIONS

REPP-TILE
Entrance Carpet Tile

Made in the USA

100% Customer Satisfaction

- REPP-Tile™ flooring is a high-performance polyester entryway tile that never has to end up in a landfill.
- REPP-Tile brings you the durability and stain resistance of recycled polyethylene terephthalate (PET) in a form that can be recycled again and again.
- When this high-performance product reaches the end of its lifecycle - typically 5 years - it can be recycled and find new life in another REPP-Tile.
- The MatWorks manages the entire process from installation to removal and recycling, meaning that your role is not only hassle-free, but you can rest assured that no materials go to waste.

Designs/Patterns

Dots

Broken Diagonal

Custom

Colors

Anthracite

Custom colors pending volume for color matching.

Specifications

Specifications	
Size	19.5" x 19.5"
Pile Height	1/32"
Overall Thickness	1/4"
Material	Polyethylene terephthalate (PET)
Material Weight	70 ounces/yard^2
Backing	REPP-Flex
Installation	TacFast or Glue-down
Performance	5 years Under normal use
100% Customer Satisfaction Based on the life of the product	

REPP-Tile Closed-Loop Lifecycle

REPP-Tile flooring eliminates the need for single-use alternatives. It is made with recycled materials that can be recycled again and again, creating a closed-loop lifecycle and a truly sustainable solution.

Flake Materials

Fabric

REPP-Tile Materials Recycled

REPP-Tile Flooring

MatWorks removes & sends back to MatWorks facility

MatWorks Installs at facility

5 year life span

CLEANING INSTRUCTIONS

MatWorks strongly recommends cleaning your carpet tiles daily to maintain functionality and appearance. The maintenance schedule should start on the installation date to achieve the maximum life expectancy of the product.

DAILY CLEANING:
- Vacuum daily with a commercial-grade vacuum cleaner with a rotary power brush or beater bar.

QUARTERLY MAINTENANCE:
- Use a high-performance, hot water extraction method a minimum of four times a year. Based on store traffic or environmental conditions such as increased salt, sand, and dirt, up to six times a year may be necessary.

SCAN FOR INSTALL GUIDE